

# Securatread

## STAIR NOSINGS

### PRODUCT DATA SHEET

## Securatread Stair Nosing

### STC6 STC6B

#### Specifications

|                    |                                                                                                    |                                  |
|--------------------|----------------------------------------------------------------------------------------------------|----------------------------------|
| Base Material      | Alloy: 6060, temper T5                                                                             |                                  |
| Finish             | Clear anodised, Black anodised                                                                     |                                  |
| Tread Width        | 70mm                                                                                               |                                  |
| Front Depth        | 10mm                                                                                               |                                  |
| Tread Thickness    | 4.8mm                                                                                              |                                  |
| Insert Type        | Solid silicon carbide - heavy duty, external grade                                                 |                                  |
| Insert Width       | 50mm                                                                                               |                                  |
| Insert Colours     | Black, yellow, dark grey and white                                                                 |                                  |
| Insert Slip Rating | P5                                                                                                 |                                  |
| Code Compliance    | AS1428.1-2021                                                                                      |                                  |
| Features           | Predrilled and countersunk for concealed screw fixings - once installed, insert covers all fixings |                                  |
| Application        | Surface mounted on hard floor surfaces                                                             |                                  |
| LRV                | Black<br>Dry 4.5<br>Wet 3.05                                                                       | Yellow<br>Dry 37.64<br>Wet 36.15 |
|                    | Light Grey<br>Dry 33.22<br>Wet 32.65                                                               | White<br>Dry 66.48<br>Wet 65.56  |

